

# JUMP STARTER & AIR INFLATOR

Two in One **20000mAh**  
**150PSI**





- ① LED Light
- ② LED Light Switch
- ③ Power Button
- ④ BAR/PSI Unit Switch Button
- ⑤ Display
- ⑥ The Button for Presetting Tire Pressure
- ⑦ Air Inflator Start-stop Button
- ⑧ Type-C Charge Port / USB-A Discharge Port
- ⑨ EC8 Starting Port
- ⑩ Air Inflator Output Port

## JUMP STARTER & AIR INFLATOR TWO IN ONE

| Parameter Specification: |                                   |
|--------------------------|-----------------------------------|
| Battery Capacity         | 20000mAh (74Wh)                   |
| Starting Voltage         | 12V                               |
| Starting Current         | 1000A                             |
| Peak Current             | 2000A                             |
| Pressure Range           | 10~150 psi                        |
| Sensor Accuracy          | ± 2psi                            |
| Input                    | USB-C 5V/3A, 9V/2A                |
| Output                   | USB-A 5V/3A, 9V/2A                |
| Polarity                 | Red(+), Black(-)                  |
| Charging Temp            | 0°C to 45°C                       |
| Operating Temp           | -20°C to 50°C                     |
| Storage Temp             | -20°C to 50°C                     |
| Battery life             | >1000 cycles<br>in good condition |
| Charging Time            | 4 to 7.5 Hours                    |

### Main Feature:

- 1) Jump Starter  
Up to 8-Liter gasoline and 6-Liter diesel  
12 V engines
- 2) Air Inflator  
Max. 150 PSI
- 3) LED Lighting  
300 LUMENS  
3 Modes: Constant Light/Strobe/SOS
- 4) Power bank  
USB-A\*1 (QC3.0, 5V3A, 9V2A)

### Certification

FC CE RoHS

